

SECTION 46 - SURVEY MONUMENTS
TABLE OF CONTENTS

Section

Page

46-1	GENERAL	46.1
46-2	MATERIALS	46.1
46-3	CONSTRUCTION	46.1
46-4	MEASUREMENT AND PAYMENT	46.1

SECTION 46 - SURVEY MONUMENTS

46-1 GENERAL

This work consists of constructing cast-in-place portland cement concrete survey monuments at the locations shown on the Plans or directed by the County Surveyor. Survey monuments must conform to the requirements in the State Specifications, these Specifications, and the Special Provisions.

The Agency will show the location and character of all existing survey monuments within the construction area on the Plans in accordance with Section 6730.2(c) of the Business and Professions Code.

Whenever a survey monument not shown on the Plans is discovered, the Contractor must immediately bring it to the attention of the Agency and must protect it.

When set forth in the Special Provisions that the Contractor is to provide all surveys, the Contractor is responsible for referencing, re-setting, and filing of corner records for all survey monuments disturbed or destroyed by construction activities in accordance with Section 8771 of the Business and Professions Code.

All survey monuments and references must be set or re-set by or under the direction of a California Licensed Land Surveyor or a California Registered Civil Engineer authorized to practice Land Surveying.

46-2 MATERIALS

Unless otherwise specified in the Contract, survey monuments must be Type D, Alternative 1, as detailed in the current State Standard Plans., except for those to be installed in new bridge deck construction. Survey monuments placed in new bridge deck construction must be modified Type A, as detailed in the current State Standard Plans, and must consist of a marker disc placed on the surface of the concrete bridge deck without specific concrete depth, reinforcing or chamfer.

Concrete must be Class "B" concrete as specified in Section 50-5, "Portland Cement Concrete", of these Specifications.

Unless otherwise specified in the Special Provisions, survey marker discs must be furnished by the Contractor and must be brass or bronze alloys. The disc must be at least 2 inches or greater in diameter and at least 2-1/2 inches long. Public Land Survey System corner monuments shall be set per the Manual of Surveying Instruction 2009.

Mortar must be as specified in the State Specifications.

46-3 CONSTRUCTION

The disc must be imbedded in fresh concrete and centered within the cross ties of the survey point.

Finished monument cases must be flush with the surrounding area and must be secured by a concrete or mortar collar as detailed on the State Plan A74. Survey monuments on new deck construction do not have monument cases.

It is essential that the survey monuments be placed in the correct locations. Survey monuments placed in locations unacceptable to the County Surveyor must be removed and replaced at the Contractor's expense.

46-4 MEASUREMENT AND PAYMENT

The quantities of each type of survey monument will be paid for as survey monuments by units, in place, determined from actual count. The unit prices paid for survey monuments include full compensation for furnishing all labor, materials, tools, equipment, and incidentals, and for doing all the work involved in constructing the survey monuments, complete in place, including monument cases, granular material, excavating and backfilling holes, and disposing of surplus excavated material, as shown or specified in the Contract, specified in these Specifications, and directed by the Agency.